

Product certificate K82923/02

Issued 2015-08-15

Replaces K82923/01

Page 1 of 3

Flushing cisterns

STATEMENT BY KIWA

With this product certificate, issued in accordance with the Kiwa Regulations for Product Certification, Kiwa declares that legitimate confidence exists that the products supplied by


SANICA ISI SANAYI A.S.

as specified in this product certificate and marked with the Kiwa®-mark in the manner as indicated in this product certificate may, on delivery, be relied upon to comply with

Kiwa evaluation guideline BRL-K620/06: "Flushing cisterns", dated 22-09-2014

which includes the requirements of

EN14055: 2010: "WC and urinal flushing cisterns".



Bouke Meekma
Kiwa

Publication of the certificate is allowed.

Advice: consult www.kiwa.nl in order to ensure that this certificate is still valid.

Kiwa Nederland B.V.

Sir Winston Churchillaan 273
P.O. Box 70
2280 AB RIJSWIJK
The Netherlands

Tel. +31 70 414 44 00
Fax +31 70 414 44 20
info@kiwa.nl
www.kiwa.nl



Supplier

SANICA ISI SANAYI A.S.
Kavakli Mahallesi, İstanbul Caddesi, No.24
34520 Beylikduzu - Istanbul
Turkey
Telephone + 90 2128558080
Telefax +90 2128558090
Internet www.sanica.com.tr

Certification process
consists of initial and
regular assessment of:

- quality system
- product

Flushing cisterns

Technical specification

Concealed flushing cisterns using a flush volume of 6 ± 0.2 litres

Model SAN125 Wall & floor

Front operated flushing cistern with dual flush operation, configuration incorporating a frame; with side connection, equipped with frame, with flush pipe and equipped with:

- float valve Fluidmaster, type 747E16B (with brass threaded connection)
- flushing device Sanica
- flexible hose Tucai
- angled connecting valve type Schell

Using various front operation panels.

Model SAN100 Standing Closet

Front operated flushing cistern with dual flush operation, with side connection, with flush pipe and equipped with:

- float valve Fluidmaster, type 747E16B (with brass threaded connection)
- flushing device Sanica
- flexible hose Tucai
- angled connecting valve type Schell

Using various front operation panels

Flushing cisterns

Application and use

Flushing cisterns (in combination with WC pans) are intended for use as flushing units connected to drinking water installations with a water temperature of maximum 30°C. Flushing cisterns using a flush volume of 6 ± 0.2 litres are intended for use in connection with WC-pans of the type 6A, according to guideline BRL-K 619.

Marking

The Kiwa®-mark products are marked with the word mark "KIWA".

Place of the mark:

- on the cisterns on the left side, right side or front or on the inside above water level;
- on the body of the float operated valve (fitting valve).

Compulsory specifications:

- name or mark of the manufacturer:

- on the float valves: on the body;
- on the cisterns: on the left side, right side or front, or on the inside above water level.
- reference to the European Standard EN14055;

Method of marking:

- indelible;
- visible after assembly (for concealed flushing cisterns, after demounting of the control panel).

RECOMMENDATIONS FOR CUSTOMERS

Check at the time of delivery whether:

- the supplier has delivered in accordance with the agreement;
- the mark and the marking method are correct;
- the products show no visible defects as a result of transport etc.

If you should reject a product on the basis of the above, please contact:

- SANICA ISI SANAYI A.S.

and, if necessary,

- Kiwa Nederland B.V.

Consult the supplier's processing guidelines for the proper storage and transport methods.